


AURRO PRECISION

PIXEL RGBW EXTERIOR LINEAR LED LIGHTING




Aurro Precision Pixel RGBW Linear LED Lighting is a Facade light like no other.

Aurro Precision Pixel RGBW lighting is used with a smart device via our App, that allow the user to program and fully control individual LEDs or groups of LEDs. Having the ability to communicate with each LED module, the level of control allows AURRO PRECISION PIXEL RGBW lighting to produce a dazzling array of lighting effects, gradient, chasing and patterns, your only limited by your imagination.



SMART HOME



EASY-TO-INSTALL



RGBW PIXEL ILLUMINATION



HOLIDAYS

FEATURES

- Simple plug and play installation
- Continuous runs of up to 55ft from one linear fixture to the next
- Choose from over 16 million colors, or simply select a warm or cool white light at a touch of a button to illuminate your home.
- Color schemes for any national holiday, season or showcase your favorite sports team. You'll never have to climb ladders to install stringer Christmas lights again!
- Fully controllable from anywhere and compatible with most low voltage Digital RGBW controllers.
- Select any light color by using a wireless remote, an app, LOVO™ Smart Voice Control or most smart home controllers.



AURRO PRECISION

PIXEL RGBW EXTERIOR LINEAR LED LIGHTING



Product Number	4300-AURROPRE-1.92W24V-RGBW
Wattage	1.2 Watts/Module / 6 Watts/M
Voltage	24VDC
Length (xin)	2M Lengths
IC Chip	UCS2904
Color Temperature	RGBW Mix 100%
Lumens	21 lm/module / 70 lm/M (Red) 67 lm/module / 220 lm/M (Green) 12 lm/module / 40lm/M (Blue) 145 lm/module / 330lm/M (RGBW White, 100%) 38lm/module / 124lm/M (White 3000K) 45lm/module / 150lm/M (White 6000K)
Wave Length	650nm to 750nm (Red) 490nm to 575nm (Green) 420nm to 490nm (Blue)
CRI	>90
Maximum Run	60Ft / 18M
Beam Angle	120 degree
Material	Aluminum Extrusion, c/w Powder Coat Paint
LED Qty	3 RGBW LED/Module (1.5 Module/ft 5 Module/M) Yes
Dimming	4"
Dimensions	2M (6.5ft) Extrusion. Holds 10 modules
IP Rating	IP68
Switching	Hardwire or Plug-in
LED Type & Size	Premium Epistar 5060
Rated Life	50,000 Hours (22 years at average of 6 hours per day.)
Warranty	3 Years
Certifications	UL Certified LED Module
Operating Temperature	-25C to +60C

ORDER CODES

MODULE

4300-AURROPRE-1.92W24V-RGBW

EXTRUSION

4300-AURROPRE-2M-


Color:
WH = White
CF = Custom Finish

AURRO PRECISION

PIXEL RGBW EXTERIOR LINEAR LED LIGHTING



DIMENSIONS





AURRO PRECISION PIXEL RGBW EXTERIOR LINEAR LED LIGHTING



RELATED PRODUCTS

APP CONTROL *Please see instructions in separate file for details.



*Other Control Options Available Upon Request

DMX PIXEL SOLUTIONS



NON DIMMING CLASS 2 POWER SUPPLIES



PLUG-IN
24 Volt with FC Connector

#5000-PSU-
Watts: 20W, 60W, 96W
Output Voltage: 24V



SINGLE OUTPUT CLASS 2
Non-Dimming Constant Voltage
UL Listed Junction Box
Input Voltage 100-277Vac

#5015-PSU- -JB-CL2
Watts: 60W, 96W
Output Voltage: 24V



MULTI-OUTPUT CLASS 2
Non-Dimming Constant Voltage
UL Listed Junction Box
Input Voltage 100-277Vac

#5040-PSU- -JB-CL2
Watts: 2x96W (192W), 3x96W (288W), 4x96W (384W)
Output Voltage: 24V

AURRO PRECISION

PIXEL RGBW EXTERIOR LINEAR LED LIGHTING



**Male AURRO STYLE
Connector to Bare Wire**
Item #4300-AURRO-5PIN-M-FC
Voltage: 24V Max
Amps: 10A
Length: 8" (200mm)
IP: IP67 Rated



**Female AURRO STYLE
Connector to Bare Wire**
Item #4300-AURRO-5PIN-F-FC
Voltage: 24V Max
Amps: 10A
Length: 8" (200mm)
IP: IP67 Rated



**Female/Male AURRO STYLE
Extension Cable**
Item #4300-AURRO-CP-F-FC
Voltage: 24V Max
Amps: 10A
Length: 8" (200mm)
IP: IP67 Rated



**Male AURRO STYLE
to Female IP67 Cable**
Item #4300-AURRO-5PIN-M-FIP67
Voltage: 24V Max
Amps: 10A
Length: 8" (200mm)
IP: IP67 Rated



**Female AURRO STYLE
to Male IP67 Cable**
Item #4300-AURRO-5PIN-F-MIP67
Voltage: 24V Max
Amps: 10A
Length: 8" (200mm)
IP: IP67 Rated



**Female AURRO STYLE
to Female IP67 Cable**
Item #4300-AURRO-5PIN-F-FIP67
Voltage: 24V Max
Amps: 10A
Length: 8" (200mm)
IP: IP67 Rated



End Cap
Item #4300-AURRO-EC-WH



End Cap with Hole
Item #4300-AURRO-EC-H-WH



Couple Plate
Item #4300-AURRO-CP-WH

AURRO PRECISION

PIXEL RGBW EXTERIOR LINEAR LED LIGHTING



LOVO™FC CONNECTORS

LOVO™FC “FAST CONNECT” CABLE SYSTEM (Please see individual spec sheets for accessory details)



Solder Tip - Male
Item #8150-FC-M-4C-4in
#8150-FC-M-4C-1ft
 24V Max 6 Amps
 4" or 12" Male to Raw
 Wire Barrel Connector



Solder Tip - Female
Item #8150-FC-F-4C-4in
#8150-FC-F-4C-1ft
 24V Max 6 Amps
 4" or 12" Female to Raw
 Wire Barrel Connector



Extensions
Item #8150-FC-EXT-4C
 Available in 3ft or 10ft
 Male to Female Extension
 Barrel Connector Cables
 24 Max 6 Amps

LOVO™FC 5C RGBW “FAST CONNECT” CABLE SYSTEM (Please see individual spec sheets for accessory details)



Solder Tip - Male
Item #8170-FC-M-5C-1ft
 1-24V Max 8 Amps
 1ft (12" / 300mm) Long
 IP67
 Male to Raw Wire Barrel
 Connector



Solder Tip - Female
Item #8170-FC-F-5C-1ft
 1-24V Max 8 Amps
 1ft (12" / 300mm) Long
 IP67
 Female to Raw Wire Barrel
 Connector



RGBW Extension Cables
Item #8170-FC-EXT-4C-3ft
#8170-FC-EXT-4C-10ft
 Available in 3ft or 10ft long
 24 Max 8 Amps
 IP67
 Male to Female Extension
 Barrel Connector Cables

LOVO™FC 5C RGBW “FAST CONNECT” SPLITTERS



MALE TO 2X FEMALE RGBW Y-SPLITTER CABLE
Item #8170-FC-2Y-5C
 24 Max 8 Amps IP67
 18" (500mm) Long
 RGBW 2-Way Y Splitter